

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

---

### SECTION 1. IDENTIFICATION

Product name : DELTADUST DP0,05  
Product code : Article/SKU: 04191098 UVP: 05952247 Specification: 102000004846 EPA Registration No: 101563-6

#### Manufacturer or supplier's details

Company name of supplier : Environmental Science U.S. LLC.  
Address : 5000 Centregreen Way, Suite 400  
Cary NC 27513  
Telephone : 1-800-331-2867  
Emergency telephone : +1 703-741-5970  
E-mail address : uscontact@envu.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Insecticide  
Restrictions on use : See product label for restrictions.

---


### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Carcinogenicity (Inhalation) : Category 1B  
Specific target organ toxicity : Category 1 (Lungs)  
- repeated exposure (Inhalation)

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : May form combustible dust concentrations in air.  
H350 May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**  
P308 + P313 IF exposed or concerned: Get medical attention.

**Storage:**  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours).  
Dust contact with the eyes can lead to mechanical irritation.  
Contact with dust can cause mechanical irritation or drying of the skin.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Dustable powder (DP)

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	$\geq 90 - \leq 100$
Quartz	14808-60-7	$\geq 1 - < 5$
Stearic acid	57-11-4	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap.  
Get medical attention if symptoms occur.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

- In case of eye contact : If in eyes, rinse well with water.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
Contact with dust can cause mechanical irritation or drying of the skin.  
Dust contact with the eyes can lead to mechanical irritation.  
This product contains a pyrethroid.  
Pyrethroid poisoning should not be confused with carbamate or organophosphate poisoning.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : There is no specific antidote available.  
Treat symptomatically.  
In case of ingestion gastric lavage should be considered in cases of significant ingestions only within the first 2 hours.  
However, the application of activated charcoal and sodium sulphate is always advisable.  
Appropriate supportive and symptomatic treatment as indicated by the patient's condition is recommended.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.  
Do not use a solid water stream as it may scatter and spread fire.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).  
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.  
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not breathe dust.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Minimize dust generation and accumulation.  
Keep container closed when not in use.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Do not eat, drink or smoke when using this product.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Explosives  
Gases

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

inert or nuisance dust	50 Million particles per cubic foot Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	15 mg/m <sup>3</sup> Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	5 mg/m <sup>3</sup> Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
	15 Million particles per cubic foot Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
Dust, nuisance dust and particulates	10 mg/m <sup>3</sup> Value type (Form of exposure): PEL (Total dust) Basis: CAL PEL
	5 mg/m <sup>3</sup> Value type (Form of exposure): PEL (respirable dust fraction) Basis: CAL PEL

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
		PEL (respirable)	0.05 mg/m <sup>3</sup>	OSHA CARC
Stearic acid	57-11-4	TWA (Inhalable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	3 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Minimize workplace exposure concentrations.  
Apply measures to prevent dust explosions.  
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazar-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

dous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white

Odor : characteristic, very faint

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : Not applicable

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	May form combustible dust concentrations in air.
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	No data available
Bulk density	:	ca. 888.999 kg/m <sup>3</sup>
Solubility(ies) Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Minimum ignition energy	:	> 10 mJ
Particle size	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	May form combustible dust concentrations in air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks. Avoid dust formation.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Limestone:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

##### **Quartz:**

Acute oral toxicity : LD50 (Rat): > 22,500 mg/kg

##### **Stearic acid:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l  
Exposure time: 1 h  
Test atmosphere: vapor  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

---

Assessment: The substance or mixture has no acute dermal toxicity

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Components:**

##### **Limestone:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

##### **Quartz:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

##### **Stearic acid:**

Species : Rabbit  
Method : Patch Test 24 Hrs.  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Components:**

##### **Limestone:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

##### **Quartz:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

##### **Stearic acid:**

Species : Rabbit  
Result : No eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

---

### Respiratory sensitization

Not classified based on available information.

#### Components:

##### **Limestone:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

##### **Stearic acid:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### **Limestone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

##### **Stearic acid:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

---

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

### **Carcinogenicity**

May cause cancer by inhalation.

#### **Product:**

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in inhalation studies with animals

#### **Components:**

##### **Quartz:**

Species : Humans  
Application Route : inhalation (dust/mist/fume)  
Result : positive

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**IARC**      Group 1: Carcinogenic to humans  
Quartz      14808-60-7  
(Silica dust, crystalline)

**OSHA**      OSHA specifically regulated carcinogen  
Quartz      14808-60-7  
(crystalline silica)

**NTP**      Known to be human carcinogen  
Quartz      14808-60-7  
(Silica, Crystalline (Respirable Size))

### **Reproductive toxicity**

Not classified based on available information.

#### **Components:**

##### **Limestone:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Result: negative  
Remarks: Based on data from similar materials

### Stearic acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

### Components:

#### Quartz:

Routes of exposure : inhalation (dust/mist/fume)  
Target Organs : Lungs  
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

### Repeated dose toxicity

### Components:

#### Limestone:

Species : Rat  
NOAEL : > 300 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 422  
Remarks : Based on data from similar materials

#### Quartz:

Species : Humans  
LOAEL : 0.053 mg/m<sup>3</sup>  
Application Route : Inhalation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

### Stearic acid:

Species	: Rat
NOAEL	: 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 42 Days
Method	: OECD Test Guideline 422
Remarks	: Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Limestone:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: LL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility. Based on data from similar materials
	: EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility. Based on data from similar materials
Toxicity to microorganisms	: EC50: > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

#### Quartz:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): 508 mg/l Exposure time: 96 h
------------------	--

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 731 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

### Stearic acid:

Toxicity to fish : LL50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l  
Exposure time: 48 h  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials  
No toxicity at the limit of solubility.

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 10 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials  
No toxicity at the limit of solubility.

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials  
No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 0.5 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials  
No toxicity at the limit of solubility.

Toxicity to microorganisms : EC10 (Pseudomonas putida): 883 mg/l  
Exposure time: 18 h

### Persistence and degradability

#### Components:

#### Stearic acid:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 71 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

### Bioaccumulative potential

#### Components:

##### Stearic acid:

Partition coefficient: n-octanol/water : log Pow: 8.23

##### Mobility in soil

No data available

##### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : It is best to use all of the product in accordance with label directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local guidelines.  
Do not dispose of waste into sewer.

Contaminated packaging : Follow advice on product label and/or leaflet.  
Empty containers retain residue and can be dangerous.  
Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Deltamethrin)  
Class : 9  
Packing group : III  
Labels : 9  
Environmentally hazardous : yes

#### IATA-DGR

UN/ID No. : UN 3077  
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Deltamethrin)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 956  
Packing instruction (passenger aircraft) : 956

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Environmentally hazardous : yes

### IMDG-Code

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Deltamethrin)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3077  
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Deltamethrin)  
Class : 9  
Packing group : III  
Labels : CLASS 9  
ERG Code : 171  
Marine pollutant : yes(Deltamethrin)  
Remarks : Above applies only to containers over 119 gallons or 450 liters.  
Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Combustible dust  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version 1.0      Revision Date: 09/14/2023      SDS Number: 11272993-00001      Date of last issue: -  
Date of first issue: 09/14/2023

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Limestone 1317-65-3  
Quartz 14808-60-7

#### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California Permissible Exposure Limits for Chemical Contaminants

Limestone 1317-65-3  
Quartz 14808-60-7


#### California Regulated Carcinogens

Quartz 14808-60-7  
Product Type : Insecticides, acaricides and products to control other arthropods  
Active substance : 0.05 %  
Deltamethrin

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	*	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

CAL PEL : California permissible exposure limits for chemical contaminants (Title 8, Article 107)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

CAL PEL / PEL : Permissible exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/14/2023	11272993-00001	Date of first issue: 09/14/2023

---

Revision Date : 09/14/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8